www.rimcled.com

Enyrio L

RIM-43020-40

Enyrio L LED Downlight Ø169mm 14-27W IP44 4000K

5-years warranty

Power	14-27 W	Voltage	230 V
Color temperature	4000 K	Color of light	Neutral White
Beam angle	40 °	Degree of protection	IP44
IK	06	UGR	<19

Available in DALI 1-10V Dimmable CASAMBI

Contact details Germany:
e.mail: info@rimcled.de
tel. +49 201 2939 7510

Contact details Dubai:
e.mail: dubaioffice@rimcled.de
tel. +971 58 572 0906

RIMCLED Licht GmbH
Wolfsbankstr.48
45355 Essen, Germany

www.rimcled.com

Technical data

Code	RIM-43020-40
Power	14-27 W
Nominal current	125 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50 Hz
Protection class	II
Power supply included	Yes
Driver Manufacturer	KGP Electronics GmbH
Power factor	0.900000
Useful luminous flux*	3250 lm (360°)
Luminous flux	1300-2600 lm (360°)
Lamp efficiency	120 lm/W
Luminous intensity	4000 cd
Color temperature	4000 K
Color of light	Neutral White
Beam angle	40 °
UGR	<19
CRI	>90
Light source included	Yes
Manufacturer LED diodes	CREE
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20°C to +40 °C
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum
Degree of protection	IP44
IK	06
Color	White
Dimensions	169x95 mm
Mounting hole	140 mm
For use	Inside
Assembly method	Recessed
Application	Inside

*applies to the LED source used

Logistics data

Bulk packaging	12 pcs
Quantity per pallet	288 pcs
Gross weight (1pcs)	0.95 kg

Contact details Germany:
e.mail: info@rimcled.de
tel. +49 201 2939 7510

Contact details Dubai:
e.mail: dubaioffice@rimcled.de
tel. +971 58 572 0906

RIMCLED Licht GmbH
Wolfsbankstr.48
45355 Essen, Germany