

Light Measurement Results

Laboratory and Equipment

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	1/17/2026

Measurement Conditions

Tested c-planes	24
Tested gamma angles	37 – 5.00°
Input Power	11.92 W


Tested Light Source

Luminaire	48V CLICK Track System LED Spot M Black 10W CCT
Basic Luminous Shape	SPOT
Item No.	
Manufacturer	RIM-40005-273340

Main Light Measurement Results


Output – Total Lumen (Up% / Down%)	770.2 lm – 0.0002% / 100%
Efficiency	64.61 lm/W
Peak Intensity	2227 cd
Correlated Color Temperature, CCT	2704 K
Color Rendering Index	CRI 91.7

Polar light distribution diagram




Light Measurement Results

Beam details




Luminaire budgetary diagram

LAMPS (number of lamps)




Light Measurement Results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)




Light Measurement Results

Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	352.3 lm	45.7%
Medium (30-60°)	32.0 lm	4.2%
High (60-80°)	0.8 lm	0.1%
Very High (80-90°)	0.1 lm	0.0%

Back Light

Low (0-30°)	352.3 lm	45.7%
Medium (30-60°)	32.0 lm	4.2%
High (60-80°)	0.8 lm	0.1%
Very High (80-90°)	0.1 lm	0.0%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	770.2 lm	100,0%
-----	----------	--------