

# Flecto S

RIM-33024-40

3-Phase 230V Track System LED Flecto S White 6,5-20W 4000K

**5-years**  
warranty



Power **6,5-20 W**  
Color temperature **4000 K**  
Beam angle **36° / 60°**

Voltage **230 V**  
Color of light **Neutral White**  
Degree of protection **IP20**

Available in



CASAMBI

## Technical data

## Logistics data

|                              |                    |                     |         |
|------------------------------|--------------------|---------------------|---------|
| Code                         | RIM-33024-40       | Bulk packaging      | 40 pcs  |
| Power                        | 6,5-20 W           | Quantity per pallet | 480 pcs |
| Nominal current              | 90 mA              | Gross weight (1pcs) | 0.36 kg |
| Voltage                      | 230 V              |                     |         |
| Energy consumption           | 20 kWh/1000h       |                     |         |
| Frequency                    | 50 Hz              |                     |         |
| Protection class             | II                 |                     |         |
| Power supply included        | Yes                |                     |         |
| Power factor                 | 0.9                |                     |         |
| Useful luminous flux*        | 2300 lm (360°)     |                     |         |
| Luminous flux                | 600-1700 lm (360°) |                     |         |
| Lamp efficiency              | 115 lm/W           |                     |         |
| Luminous intensity           | 3800 cd            |                     |         |
| Color temperature            | 4000 K             |                     |         |
| Color of light               | Neutral White      |                     |         |
| Beam angle                   | 36° / 60°          |                     |         |
| CRI                          | >90                |                     |         |
| Light source included        | Yes                |                     |         |
| Uniformity of color SDCM max | 5                  |                     |         |
| Dimmable                     | No                 |                     |         |
| Working temperature range    | -20°C to +40 °C    |                     |         |
| Warranty                     | 5 years            |                     |         |
| Lifespan                     | 50000 h            |                     |         |
| (On/Off)                     | 25000              |                     |         |
| Housing material             | Aluminum           |                     |         |
| Degree of protection (IP)    | IP20               |                     |         |
| Color                        | White              |                     |         |
| Dimension                    | 75x78x124 mm       |                     |         |
| For use                      | Inside             |                     |         |
| Assembly method              | on 230V track      |                     |         |
| Application                  | Inside             |                     |         |

\*applies to the LED source used

