

Grid S

RIM-40011-273340

48V CLICK Track System LED Grid S Black 12W CCT

5-years
warranty



| | | | |
|----------------------|-------------------------|----------------|---------------|
| Power | 12 W | Voltage | 48 V |
| Color temperature | 2700/3300/4000 K | Color of light | CCT |
| Beam angle | 35 ° | UGR | <19 |
| Degree of protection | IP20 | | |

Available in



CASAMBI

Technical data

Logistics data

| | |
|------------------------------|------------------|
| Code | RIM-40011-273340 |
| Power | 12 W |
| Nominal current | 230 mA |
| Voltage | 48 V |
| Energy consumption | 12 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power supply included | Yes |
| Power factor | 1 |
| Useful luminous flux* | 1200 lm (360°) |
| Luminous flux | 750 lm (360°) |
| Lamp efficiency | 100 lm/W |
| Luminous intensity | 2580 cd |
| Color temperature | 2700/3300/4000 K |
| Color of light | CCT |
| Beam angle | 35 ° |
| UGR | <19 |
| CRI | >90 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20°C to +40 °C |
| Warranty | 5 years |
| Lifespan | 50000 h |
| (On/Off) | 25000 |
| Housing material | AL + PC |
| Degree of protection (IP) | IP20 |
| Color | Black |
| Dimension (AxBxC) | 220x23x42 mm |
| For use | Inside |
| Assembly method | on 48V track |
| Application | Inside |

| | |
|---------------------|----------|
| Bulk packaging | 50 pcs |
| Quantity per pallet | 1800 pcs |
| Gross weight (1pcs) | 0.18 kg |

*applies to the LED source used

