www.rimcled.com

Flexiron S

RIM-20110-30

Flexiron S LED Downlight 7W Ø72mm IP20 Black 3000K

5-years warranty

Power	7 W	Voltage	230 V
Color temperature	3000 K	Color of light	Warm White
Beam angle	36 °	Degree of protection	IP20
IK	06	CRI	>90

Available in DALI 1-10V Dimmable CASAMBI

Contact details Germany:
e.mail: info@rimcled.de
tel. +49 201 2939 7510

Contact details Dubai:
e.mail: dubaioffice@rimcled.de
tel. +971 58 572 0906

RIMCLED Licht GmbH
Wolfsbankstr.48
45355 Essen, Germany

www.rimcled.com

Technical data

Code	RIM-20110-30
Power	7 W
Nominal current	160 mA
Voltage	230 V
Energy consumption	7 kWh/1000h
Frequency	50 Hz
Protection class	II
Power supply included	Yes
Driver Manufacturer	KGP Electronics GmbH
Power factor	0.9
Useful luminous flux*	637 lm (360°)
Luminous flux	476 lm (360°)
Lamp efficiency	91 lm/W
Luminous intensity	1260 cd
Color temperature	3000 K
Color of light	Warm White
Beam angle	36 °
CRI	>90
Light source included	Yes
Manufacturer LED diodes	CREE
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20°C to +40 °C
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	AL + PC
Degree of protection	IP20
IK	06
Color	Black
Dimensions	72X100 mm
Mounting hole	62 mm
For use	Inside
Assembly method	Recessed
Application	Inside

*applies to the LED source used

Logistics data

Bulk packaging	40 pcs
Quantity per pallet	800 pcs
Gross weight (1pcs)	0.32 kg

Contact details Germany:
e.mail: info@rimcled.de
tel. +49 201 2939 7510

Contact details Dubai:
e.mail: dubaioffice@rimcled.de
tel. +971 58 572 0906

RIMCLED Licht GmbH
Wolfsbankstr.48
45355 Essen, Germany