

Flecto M

RIM-33025-40

3-Phase 230V Track System LED Flecto M Black 12-42W 4000K

5-years
warranty



Power **12-42 W**
Color temperature **4000 K**
Beam angle **36° / 60°**

Voltage **230 V**
Color of light **Neutral White**
Degree of protection **IP20**

Available in



CASAMBI

Technical data

Logistics data

| | | | |
|------------------------------|---------------------|---------------------|---------|
| Code | RIM-33025-40 | Bulk packaging | 20 pcs |
| Power | 12-42 W | Quantity per pallet | 320 pcs |
| Nominal current | 180 mA | Gross weight (1pcs) | 0.69 kg |
| Voltage | 230 V | | |
| Energy consumption | 42 kWh/1000h | | |
| Frequency | 50 Hz | | |
| Protection class | II | | |
| Power supply included | Yes | | |
| Power factor | 0.9 | | |
| Useful luminous flux* | 4500 lm (360°) | | |
| Luminous flux | 1300-3800 lm (360°) | | |
| Lamp efficiency | 107 lm/W | | |
| Luminous intensity | 8900 cd | | |
| Color temperature | 4000 K | | |
| Color of light | Neutral White | | |
| Beam angle | 36° / 60° | | |
| CRI | >90 | | |
| Light source included | Yes | | |
| Uniformity of color SDCM max | 5 | | |
| Dimmable | No | | |
| Working temperature range | -20°C to +40 °C | | |
| Warranty | 5 years | | |
| Lifespan | 50000 h | | |
| (On/Off) | 25000 | | |
| Housing material | Aluminum | | |
| Degree of protection (IP) | IP20 | | |
| Color | Black | | |
| Dimension | 100x96x157 mm | | |
| For use | Inside | | |
| Assembly method | on 230V track | | |
| Application | Inside | | |

*applies to the LED source used

