

Light Measurement Results

Laboratory and Equipment

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	1/30/2026

Measurement Conditions

Tested c-planes	24
Tested gamma angles	37 – 5.00°
Input Power	12.45 W


Tested Light Source

Luminaire	RIM-20111-30
Basic Luminous Shape	SPOT
Item No.	
Manufacturer	RIMCLED

Main Light Measurement Results


Output – Total Lumen (Up% / Down%)	770.4 lm – 0.0042% / 100%
Efficiency	61.88 lm/W
Peak Intensity	1571 cd
Correlated Color Temperature, CCT	3100 K
Color Rendering Index	CRI 97.9

Polar light distribution diagram




Light Measurement Results

Beam details




Luminaire budgetary diagram

LAMPS (number of lamps)




Light Measurement Results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)




Light Measurement Results

Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Beam Angle	lm	%
Low (0-30°)	312.3 lm	40.5%
Medium (30-60°)	63.6 lm	8.2%
High (60-80°)	6.2 lm	0.8%
Very High (80-90°)	3.1 lm	0.4%

Back Light

Beam Angle	lm	%
Low (0-30°)	312.3 lm	40.5%
Medium (30-60°)	63.6 lm	8.2%
High (60-80°)	6.2 lm	0.8%
Very High (80-90°)	3.1 lm	0.4%

Uplight

Beam Angle	lm	%
Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	770.4 lm	100,0%
-----	----------	--------