

# Enyrio M

RIM-43019-40

Enyrio M LED Downlight Ø139mm 6-20W IP44 4000K

**5-years**  
warranty



Power **6-20 W**  
Color temperature **4000 K**  
Beam angle **40 °**  
IK **06**

Voltage **230 V**  
Color of light **Neutral White**  
Degree of protection **IP44**  
UGR **<19**

Available in



**1-10V**  
Dimmable

CASAMBI

## Technical data

## Logistics data

Code	RIM-43019-40
Power	6-20 W
Nominal current	90 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50 Hz
Protection class	II
Power supply included	Yes
Driver Manufacturer	KGP Electronics GmbH
Power factor	0.900000
Useful luminous flux*	2400 lm (360°)
Luminous flux	600-1900 lm (360°)
Lamp efficiency	120 lm/W
Luminous intensity	3100 cd
Color temperature	4000 K
Color of light	Neutral White
Beam angle	40 °
UGR	<19
CRI	>90
Light source included	Yes
Manufacturer LED diodes	CREE
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20°C to +40 °C
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum
Degree of protection	IP44
IK	06
Color	White
Dimensions	139x85 mm
Mounting hole	115 mm
For use	Inside
Assembly method	Recessed
Application	Inside

Bulk packaging	24 pcs
Quantity per pallet	360 pcs
Gross weight (1pcs)	0.64 kg

\*applies to the LED source used

