

# Enyrio L

RIM-43020-30

Enyrio L LED Downlight Ø169mm 14-27W IP44 3000K

**5-years**  
warranty



|                   |                |                      |                   |
|-------------------|----------------|----------------------|-------------------|
| Power             | <b>14-27 W</b> | Voltage              | <b>230 V</b>      |
| Color temperature | <b>3000 K</b>  | Color of light       | <b>Warm White</b> |
| Beam angle        | <b>40 °</b>    | Degree of protection | <b>IP44</b>       |
| IK                | <b>06</b>      | UGR                  | <b>&lt;19</b>     |

Available in



**1-10V**  
Dimmable

CASAMBI

## Technical data

## Logistics data

|                              |                      |
|------------------------------|----------------------|
| Code                         | RIM-43020-30         |
| Power                        | 14-27 W              |
| Nominal current              | 125 mA               |
| Voltage                      | 230 V                |
| Energy consumption           | 27 kWh/1000h         |
| Frequency                    | 50 Hz                |
| Protection class             | II                   |
| Power supply included        | Yes                  |
| Driver Manufacturer          | KGP Electronics GmbH |
| Power factor                 | 0.900000             |
| Useful luminous flux*        | 3000 lm (360°)       |
| Luminous flux                | 1200-2300 lm (360°)  |
| Lamp efficiency              | 110 lm/W             |
| Luminous intensity           | 3300 cd              |
| Color temperature            | 3000 K               |
| Color of light               | Warm White           |
| Beam angle                   | 40 °                 |
| UGR                          | <19                  |
| CRI                          | >90                  |
| Light source included        | Yes                  |
| Manufacturer LED diodes      | CREE                 |
| Uniformity of color SDCM max | 5                    |
| Dimmable                     | No                   |
| Working temperature range    | -20°C to +40 °C      |
| Warranty                     | 5 years              |
| Lifespan                     | 50000 h              |
| (On/Off)                     | 25000                |
| Housing material             | Aluminum             |
| Degree of protection         | IP44                 |
| IK                           | 06                   |
| Color                        | White                |
| Dimensions                   | 169x95 mm            |
| Mounting hole                | 140 mm               |
| For use                      | Inside               |
| Assembly method              | Recessed             |
| Application                  | Inside               |

|                     |         |
|---------------------|---------|
| Bulk packaging      | 12 pcs  |
| Quantity per pallet | 288 pcs |
| Gross weight (1pcs) | 0.95 kg |

\*applies to the LED source used

